



EXTRA HEAVY DUTY SPRING LOADED TILLER



BENEFITS:

- Suitable for use in stone and root obstructed soil. It is designed for toughest operations.
- Used for loosening and aerating soil to a depth of nine inches.
- Prepares seed beds quickly and economically.

FEATURES:

- When one tyne strikes a hidden object, the others continue to work at the correct depth.
- Spring Loaded assemblies derive their strength from heavy-duty angles, which once fixed to the immensely strong main frame cannot move or strain out of position.

SPECIFICATIONS:

	9 TYNE	11 TYNE	13 TYNE	15 TYNE
FRAME	75 x 40 mm (Channel)	75 x 40 mm (Channel)	100X50 mm (Channel)	100X50 mm (Channel)
SPRING	10 mm WD, 50 mm OD 28.5 Coils	10 mm WD, 50 mm OD 28.5 Coils	10 mm WD, 50 mm OD 28.5 Coils	10 mm WD, 50 mm OD 28.5 Coils
TYNES	50 x 25 mm (Forged)	50 x 25 mm (Forged)	50 x 25 mm (Forged)	50 x 25 mm (Forged)
PAIRS	65x65x 6 mm Angle (Main Steel)	65x65x 6 mm Angle (Main Steel)	65x65x 6 mm Angle (Main Steel)	65x65x 6 mm Angle (Main Steel)
ANCHOR PIN	22 mm	22 mm	22 mm	22 mm
NUTS	High Tensile	High Tensile	High Tensile	High Tensile
FRAME BOLT	M 12 x 35 (High Tensile)	M 12 x 35 (High Tensile)	M 12 x 35 (High Tensile)	M 12 x 35 (High Tensile)
TYNE BOLT	M 18 x 65 mm (High Tensile)	M 18 x 65 mm (High Tensile)	M 18 x 65 mm (High Tensile)	M 18 x 65 mm (High Tensile)
LINKAGE 3 POINT	50 x 16 mm (Rear) 50 x 16 mm (Front)	50 x 16 mm (Rear) 50 x 16 mm (Front)	50 x 16 mm (Rear) 50 x 16 mm (Front)	50 x 16 mm (Rear) 50 x 16 mm (Front)
SHOVEL	8 mm EN-45	8 mm EN-45	8 mm EN-45	8 mm EN-45
LENGTH	2000 mm	2457 mm	2914 mm	3371 mm
WIDTH	850 mm	850 mm	850 mm	850 mm
HEIGHT	585 mm	585 mm	585 mm	585 mm
TILLER PIN	28 mm	28 mm	28 mm	28 mm
WEIGHT	280 Kg.	340 Kg.	450 Kg.	515 Kg.

*The weight and working data contained in the present leaflet are supplied for information only and are not binding. Specification and size can be altered as part of ongoing product modification/improvement.