



HEAVY DUTY LAND LEVELLER



BENEFITS:

- It is a simple and rugged Implement which is directly fitted to the tractor.
- The 10mm single plate duly reinforced makes our leveler trouble free in operation.
- It is a basic implement for leveling of land.

FEATURES:

- Leveling blade is made out of special steel which gives it double the life compared to other ordinary blades.
- The leveler is available with 6, 7 and 8 ft width.

SPECIFICATIONS:

	6 FEET	7 FEET	8 FEET
FRAME	Draw Bar mounting with the help of MS Flat section 75 x 20mm, 520mm Long		
SIDE SUPPORT	Vertical : 25 x 10mm MS Flat Horizontal: Crescent shape, MS Flat, Max. width 100mm, Min. width 35mm		
THICKNESS OF PLATE	10 mm		
BLADE DIM.	70 x 10mm (High carbon steel)		
3 POINT LINKAGE	65x16 mm Flat		
CENTRAL SUPPORT	MS Angle 40 x 5mm		
LINKAGE PIN	28mm		
SPAN	1850mm	2150mm	2460 mm
WEIGHT	140 Kg. (approx)	155 Kg. (approx)	170 Kg. (approx)

*The weight and working data contained in the present leaflet are supplied for information only and are not binding. Specification and size can be altered as part of ongoing product modification/improvement.

Agra Engineering Co.

C-5 Laxmi Towers, Bandra Kurla Complex, Bandra (East), Mumbai 400 051, India.
Telephone: +91 22 675 44 555 (100 Lines) Fax: +91 22 675 44 544
URL: www.aeco.co.in email: enquiry@aeco.co.in