



MEDIUM DUTY RIGID TYPE TILLER



BENEFITS:

- It is designed to withstand toughest work and operates as a Light Chisel Plough.
- Used for loosening and aerating soil to a depth of nine inches.

FEATURES:

- The tiller has heavy duty shanks for positive penetration.
- It breaks up hard top soil, uproots stubble and leaves the ground perfectly worked.
- It is particularly useful for paddy cultivation areas requiring shallow ploughing on hard clayey cracked up soil. In such places it prepares seed bed faster than ploughing.

SPECIFICATIONS:

	9 TYNE	11 TYNE
FRAME	65x8mm (Angle) Box Frame	65x8mm (Angle) Box Frame
TYNES	75X25mm Flat with Rakab (U Clamp)	75X25mm Flat with Rakab (U Clamp)
SIDE SUPPORT	100X12 mm Flat	100X12 mm Flat
SHOVELS	En-45, 10mm	En-45, 10mm
FRAME BOLT	18X65 mm	18X65 mm
THREE POINT LINKAGE	65X16 Front 50X16 Rear	65X16 Front 50X16 Rear
HEIGHT	25.5"	25.5"
LENGTH	79"	97"
WIDTH	30.5"	30.5"
WEIGHT	242 Kgs. (Approx.)	295 Kgs. (Approx.)

*The weight and working data contained in the present leaflet are supplied for information only and are not binding. Specification and size can be altered as part of ongoing product modification/improvement.

Agra Engineering Co.

C-5 Laxmi Towers, Bandra Kurla Complex, Bandra (East), Mumbai 400 051, India

Telephone: +91 22 675 44 555 (100 Lines) Fax: +91 22 675 44 544

URL: www.agraeng.com email: agra@agraeng.com