



MOUNTED MEDIUM DUTY OFFSET DISC HARROW



BENEFITS:

- Used in open field workings for the superficial ploughing, for the shattering of clods, preparation of soil for sowing, burial of organic substances & remains.
- To air the soil and to eliminate the weeds.
- For breaking the roots.
- It has low purchasing and utilization costs both for its wide working width, and for its high speed (from 7 to 15 km/hour).
- Angle can be easily adjustable.
- It can be used in light and medium soil.

FEATURES:

- High quality steel discs.
- Tillage depth of the harrow is 6 inch.
- Easily transportable. As it gets easily attached and mounted.
- Maintenance is easy but need to be scheduled.

SPECIFICATIONS:

	6 X 6	7 X 7	8X8	9X9	10X10
No. OF DISCS	12	14	16	18	20
FRAME	75 x10mm Angle with 100 x 50 mm Channel	75 x10mm Angle with 100 x 50 mm Channel	75 x10mm Angle with 100 x 50 mm Channel	75 x10mm Angle with 100 x 50 mm Channel	75 x10mm Angle with 100 x 50 mm Channel
GANG BOLT	Central Square Solid Bar	Central Square Solid Bar	Central Square Solid Bar	Central Square Solid Bar With split gangs	Central Square Solid Bar With split gangs
LENGTH	2030 mm	2080 mm	2130 mm	2230 mm	2280 mm
HEIGHT	1150 mm with 560mm Disc 1200 mm with 610mm Disc	1150 mm with 560mm Disc 1200 mm with 610mm Disc	1150 mm with 560mm Disc 1200 mm with 610mm Disc	1150 mm with 560mm Disc 1200 mm with 610mm Disc	1150 mm with 560mm Disc 1200 mm with 610mm Disc
DISTANCE BETWEEN DISCS	225 mm	225 mm	225 mm	225 mm	225 mm
MOUNTING	CAT I/ II (Optional)	CAT I/ II (Optional)	CAT I/ II (Optional)	CAT I/ II (Optional)	CAT I/ II (Optional)
DISC DIAMETER (mm)	560/610 (Optional)	560/610 (Optional)	560/610 (Optional)	560/610 (Optional)	560/610 (Optional)
TYPE OF DISCS	Notched in Front & Plain in Rear	Notched in Front & Plain in Rear	Notched in Front & Plain in Rear	Notched in Front & Plain in Rear	Notched in Front & Plain in Rear
BEARING HUBS (Nos.)	4	4	6	8 (Split Gang Arrangement)	8 (Split Gang Arrangement)
WIDTH OF CUT	1375. 1400 mm	1600. 1625 mm	1825. 1850 mm	2050. 2075 mm	2275. 2300mm
WEIGHT (KG) (approx)	400 with 560 mm Disc 424with 610 mm Disc	435 with 560 mm Disc 463 with 610 mm Disc	480 with 560 mm Disc 512 with 610 mm Disc	535 with 560 mm Disc 565 with 610 mm Disc	570 with 560 mm Disc 620 with 610 mm Disc
POWER REQUIRED (HP)	30-35	40-45	45-50	50-55	55-65

*The weight and working data contained in the present leaflet are supplied for information only and are not binding. Specification and size can be altered as part of ongoing product modification/improvement.

Agra Engineering Co.

C-5 Laxmi Towers, Bandra Kurla Complex, Bandra (East), Mumbai 400 051, India

Telephone: +91 22 675 44 555 (100 Lines)

Fax: +91 22 675 44 544

URL: www.agraeng.com

email: agra@agraeng.com