



## MOUNTED MEDIUM TANDEM DISC HARROW



### BENEFITS:

- Used in open field workings for the superficial ploughing, for the shattering of clods, preparation of soil for sowing, burial of organic substances & remains.
- To air the soil and to eliminate the weeds.
- For breaking the roots.
- It can be used in light and medium soil.

### FEATURES:

- High quality Boron steel discs.
- Tillage depth of the harrow is 6 inch.
- Easily transportable- as it gets easily attached and mounted.
- Maintenance is easy but need to be scheduled.
- One Tyne in rear side to cover the central area.

### SPECIFICATIONS:

	8X8	9X9	10X10
FRAME	Square Pipe Box Frame	Square Pipe Box Frame	Square Pipe Box Frame
GANG BOLT	Central Square Solid Bar With split gangs	Central Square Solid Bar With split gangs	Central Square Solid Bar With split gangs
LENGTH	1867 mm	1867 mm	1867 mm
WIDTH	1867 mm	2095 mm	2325 mm
NO. OF DISC	16	18	20
TYPE OF DISC	Notched (Front/Rear)	Notched (Front/Rear)	Notched (Front/Rear)
DISC DIAMETER	560 mm	560 mm	560 mm
WIDHT OF CUT	1778 mm	2006 mm	2235 mm
DISTANCE BETWEEN DISCS	228 mm	228 mm	228 mm
BEARING HUBS	8	8	8
TOTAL HEIGHT	1080 mm	1080 mm	1080 mm
MAST HEIGHT	1054 mm	1054 mm	1054 mm
TYNE WITH SPRING	1	1	1
WEIGHT (KGS.) (Approx.)	565	595	627
POWER REQUIRED (HP)	45-50	50-55	55-60

\*The weight and working data contained in the present leaflet are supplied for information only and are not binding. Specification and size can be altered as part of ongoing product modification/improvement.

Agra Engineering Co.

C-5 Laxmi Towers, Bandra Kurla Complex, Bandra (East), Mumbai 400 051, India

Telephone: +91 22 675 44 555 (100 Lines)

Fax: +91 22 675 44 544

URL: [www.agraeng.com](http://www.agraeng.com)

email: [agra@agraeng.com](mailto:agra@agraeng.com)