



## ROTARY TILLER (SINGLE SPEED)



### BENEFITS:

- Suitable for use in dry as well as wet land cultivation.
- Suitable for light and medium soil conditions.
- Used for loosening and aerating soil up to a depth of 5-6 inches.
- Prepares seed beds quickly and economically.

### FEATURES:

- Single speed gear box with 3 Point linkage, Compatible with 540 PTO RPM.
- Easy depth adjustment.
- Available in both gear driven and chain driven.
- Type of blade- L type.

### SPECIFICATIONS:

	AE 125	AE 150	AE 175	AE 200
<b>TRACTOR POWER</b>	40-45	45-50	50-55	55-65
<b>OVERALL WIDTH</b>	155 cm	180 cm	205 cm	230 cm
<b>TILLAGE WIDTH</b>	125 cm	150 cm	175 cm	200 cm
<b>GEAR BOX</b>	SINGLE SPEED	SINGLE SPEED	SINGLE SPEED	SINGLE SPEED
<b>P.T.O. SPEED (r.p.m.)</b>	540	540	540/540	540
<b>ROTOR SPEED</b>	210	210	210	210
<b>GEAR BOX OVERLOAD PROTECTION</b>	SHEAR BOLT	SHEAR BOLT	SHEAR BOLT	SHEAR BOLT
<b>MOUNTING HEIGHT</b>	117 cm	117 cm	117 cm	117 cm
<b>No. OF FLANGES</b>	5	6	7	7
<b>No. OF BLADES</b>	30	36	42	48
<b>TOTAL WT.</b>	297 Kg. (Approx.)	337 Kg. (Approx.)	377 Kg. (Approx.)	417 Kg. (Approx.)

\*The weight and working data contained in the present leaflet are supplied for information only and are not binding. Specification and size can be altered as part of ongoing product modification/improvement.

Agra Engineering Co.

C-5 Laxmi Towers, Bandra Kurla Complex, Bandra (East), Mumbai 400 051, India

Telephone: +91 22 675 44 555 (100 Lines) Fax: +91 22 675 44 544

URL: [www.agraeng.com](http://www.agraeng.com) email: [agra@agraeng.com](mailto:agra@agraeng.com)