



ROTO TILL SPEED DRILL



ROTO TILL SPEED DRILL is a one-pass Agricultural implement which we used for the purpose of land preparation in the agriculture fields. ROTO TILL SPEED DRILL is a rotary tillage implement driven by tractor's power take off shaft (PTO Shaft), which cuts, pulverizes & mixes the soil and residue in a single pass.

Both the Tractor and ROTO TILL SPEED DRILL are safe-guarded by shear bolt PTO drive shaft which shears off when the blades gets encountered by stumps, stones or some other thing and gets overloaded.

ONLY DIFFERENCE IS ADDITION OF NINE ROW SEED CUM FERTILIZER DRILL.

SPECIFICATIONS:

Working width:	184 cm	125 cm
H.P. Required:	45-60 H.P.	35-40 H.P.
No. of Flange:	9	6
No. of blades per flange.	4	4
Total no of blades:	36	24
Flange pitch:	20 cm	
Working Depth:	2 cm to 15 cm (Adjustable)	
Depth Control:	By Skids on both sides	
PTO Seed:	540 rpm	
Rotor Speed:	230 rpm	
Hitching:	Three point linkage	
Blades:	Breviglieri Italy (Imported) replaceable	
Chain Drive :	Duplex	

*The weight and working data contained in the present leaflet are supplied for information only and are not binding. Specification and size can be altered as part of ongoing product modification/improvement.

Agra Engineering Co.

C-5 Laxmi Towers, Bandra Kurla Complex, Bandra (East), Mumbai 400 051, India.

Telephone: +91 22 675 44 555 (100 Lines) Fax: +91 22 675 44 544

URL: www.aeco.co.in email: enquiry@aeco.co.in