



## SPRING LOADED TILLER



### BENEFITS:

- It is designed for the light and medium soils.
- Used for loosening and aerating soil to a depth of nine inches.
- Prepares seed beds quickly and economically.

### FEATURES:

- When one tyne strikes a hidden object, the others continue to work at the correct depth.

### SPECIFICATIONS:

	<b>9 TYNE</b>	<b>11 TYNE</b>
<b>FRAME</b>	75 x 40 mm (Channel)	75 x 40 mm (Channel)
<b>SPRING</b>	9.5 mm WD, 50 mm OD 27 Coils	9.5 mm WD, 50 mm OD 27 Coils
<b>TYNES</b>	50 x 19 mm (Forged)	50 x 19 mm (Forged)
<b>PAIRS</b>	50X8 mm Flat	50X8 mm Flat
<b>ANCHOR PIN</b>	25 mm	25 mm
<b>NUTS</b>	Nylock	Nylock
<b>FRAME BOLT</b>	M 12 x 32 (High Tensile)	M 12 x 32 (High Tensile)
<b>TYNE BOLT</b>	16X90 mm	16X90 mm
<b>LINKAGE 3 POINT</b>	50 X 12 mm	50 X 12 mm
<b>SHOVEL</b>	8 mm EN-45	8 mm EN-45
<b>LENGTH</b>	2000 mm	2457 mm
<b>WIDTH</b>	712 mm	712 mm
<b>HEIGHT</b>	533 mm	533 mm
<b>TILLER PIN</b>	28 mm	28 mm
<b>WEIGHT</b>	215 Kg. (Approx.)	265 Kg. (Approx.)

\*The weight and working data contained in the present leaflet are supplied for information only and are not binding. Specification and size can be altered as part of ongoing product modification/improvement.

### Agra Engineering Co.

C-5 Laxmi Towers, Bandra Kurla Complex, Bandra (East), Mumbai 400 051, India.  
Telephone: +91 22 675 44 555 (100 Lines) Fax: +91 22 675 44 544  
URL: [www.aeco.co.in](http://www.aeco.co.in) email: [enquiry@aeco.co.in](mailto:enquiry@aeco.co.in)