

## PLOUGH DISC



Dia-meter	Refer-ence	Thick-ness	Conca-vity	Conca-vity Inches	Hold Size	Hold Size Inches	Hole Shape	Axle	Axle inches	Edge	Bevel	Bolt Qty	Bolt size	Radius to fit bolt
22	L2203	4	60	2-3/8	Ø63.0	Ø2-1/2	ROUND			EXT	EXT	4	10,8	55
24	L2404	4,5	74	2 7/8	27	1-1/16	ROUND			INT	EXT	4	13,5	114,3
24	L2492	6	25,4	1	117,4	Ø4-5/8	ROUND	-	-	EXT	EXT	6	13,5	76,2
24	L2495	6	74	2 7/8	27	1-1/16	ROUND	25,4	1	INT	EXT	4	13,5	114,3
26	L2652	6	99	3-7/8	Ø27.0	Ø1-1/16	ROUND	Ø25.5	1	INT	EXT	5	13,5	142,9
26	L2622	6	99	3-7/8	Ø27.0	Ø1-1/16	ROUND			INT	EXT	5	13,5	104,8
26	L2621	6	99	3-7/8	Ø27.0	Ø1-1/16	ROUND			INT	EXT	4	13,5	115
26	L2609	5	97	3-7/8	Ø26.6	1-1/16	ROUND			INT	EXT	5	13,5	142,9
26	L2601	5	97	3-13/16	Ø26.4	Ø1-1/16	ROUND			INT	EXT	5	13,5	104,8
26	L2600	5	89	3-1/2	Ø26.4	Ø1-1/16	ROUND			INT	EXT	4	13,5	114,3
28	L2800	6	110	4-1/4	Ø27.0	Ø1-1/16	ROUND			INT	EXT	4	13,5	115,1
28	L2801	6	110	4-1/4	Ø27.0	Ø1-1/16	ROUND			INT	EXT	5	13,5	105
28	L2803	6	110	4-1/4	Ø27.0	Ø1-1/16	ROUND			INT	EXT	5	13,5	143
28	L2812	6	110	4-1/4	Ø27.0	Ø1-1/16	ROUND			INT	EXT	6	13,5	87,3
28	L2878	7,5	110	4-1/4	Ø27.0	Ø1-1/16	ROUND			INT	EXT	4	13,5	115,1
28	L2881	7,5	110	4-1/4	Ø27.0	Ø1-1/16	ROUND			INT	EXT	5	13,5	143